

EPIC® MC Dummy Module

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

The blinding module is ideal for reserving a space for later use. It is suitable for printing presses or control systems.

Info

Dummy module as a placeholder for future expansion





Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications

Application range

Plant engineering Printing machines Control engineering

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial

connector)

Classification ETIM 6: ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial

connector)

Temperature range: -40°C to +100°C, short-term up to +125°C



EPIC® MC Dummy Module

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® MC Dummy Module

Contact type Slots Pieces / PU Article number Article description Dummy module MCS 0 Blind 10 10399400 male MCB 0 Blind 10 10399500 female