

ÖLFLEX® TRAIN 325 C TW-E 300V

Screened multi-core cable according to EN 50306-4 3E type MM S for high requirements in railway applications

ÖLFLEX® TRAIN 325 C TW-E 300V - control cable shielded according to EN 50306-4 3E type MM S, 300/500V for rail vehicles/trains, EN 45545: HL1-HL3, NF F 16-101: C/F0

Info

Meets EN 50306-4 class E, type MM S and EN 45545-2

High temperature resistance: -50 °C up to +125 °C

Highly oil- and fuel-resistant



LAPP KABEL STUTTGART ÖLFLEX® TRAIN 325 C TW-E 300V EN 50306-4 3E MM S



Rail



Good chemical resistance



Flame-retardant



Halogen-free



Cold-resistant



Mechanical resistance



Oil-resistant



Space requirement

Last Update (24.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® TRAIN 325 C TW-E 300V



Interference signals



Temperature-resistant



UV-resistant

Benefits

Reduced insulation wall thickness, thus space-saving installation

Copper screening complies with EMC requirements and protects against electromagnetic interference

Resistant to mechanical influences in harsh environmental conditions

Extended temperature range

Reduced flame spreading increases the protection against damage to persons and property in the event of a fire

Application range

In EMC-sensitive environments

For use in railway vehicles, for fixed installations and applications where limited movement may occur

Suitable for control and monitoring circuits as well as locking circuits and internal wiring of equipment in trains and locomotives

Also applicable within oily environments and areas with increased ambient temperature

Product features

Fire behaviour according to EN/IEC:

- Halogen-free acc. to EN 60754-1
- No corrosive gases acc. to EN 60754-2
- No fluorine acc. to EN 60684-2
- No toxic gases acc. to EN 50305
- Low smoke density acc. to EN 61034-2
- Flame-retardant acc. to EN 60332-1-2
- No flame propagation acc. to

EN 60332-3-24 / EN 60332-3-25 /

EN 50305

Fire behaviour according to NF:

- Toxicity of gases acc. to NF X 70-100
- Low smoke density acc. to NF X 10-702
- No flame propagation acc. to NF C 32-070,
Cat. C1 and C2

Chemical properties:

- Oil resistant acc. to EN 50306
- Fuel resistant acc. to EN 50306
- Acid resistant acc. to EN 50306
- Alkali resistant acc. to EN 50306
- Ozone resistant acc. to EN 50306

Current rating according to EN 50355, appendix A

Norm references / Approvals

EN 50306-4 class E, type MM S

EN 45545-2 HL1, HL2, HL3

NF F 16-101 - Classification: C / F0

(flame propagation / smoke)

Product Make-up

Last Update (24.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® TRAIN 325 C TW-E 300V

Outer sheath colour: Black

Tinned-copper strand, 19 or 37 wires, SRC (Special Round Conductor)

Insulation: Electron beam cross-linked Polymer compound acc. to EN 50306

Colour of insulation: White with black numbers

Wrapping: Halogen-free plastic foil (optional)

Screen: Tinned-copper braiding

The cross-linked polymer compound is highly resistant to oils, fuels, alkalis and acids.

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	White with black numbers
Conductor stranding:	SRC (special round conductor) 19 or 37 wires acc. to EN 50306-1
Minimum bending radius:	Fixed installation: 5 x outer diameter Occasional flexing: 10 x outer diameter
Nominal voltage:	U ₀ : 600 V AC U ₀ /U: 300/500 V AC acc. to EN 50306 U _m : 550 V AC
Test voltage:	3,5 kV AC; 8,4 kV DC
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Fixed installation: -45°C to +125°C (20.000 h) -50°C acc. to GOST 20.57.406-81 Occasional flexing: -35°C to +105°C Short circuit: +160°C (5s)

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® TRAIN 325 C TW-E 300V

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
15325000	2 X 0.5	6.0	19.37	57.36
15325001	3 X 0.5	6.2	24.88	64.85
15325002	4 X 0.5	6.6	30.87	74.62
15325003	6 X 0.5	7.4	42.95	95.06
15325004	8 X 0.5	8.0	61.26	121.54
15325005	2 X 0.75	6.4	25.67	65.89
15325006	3 X 0.75	6.7	33.71	78.02
15325007	4 X 0.75	7.0	42.18	89.21
15325008	6 X 0.75	8.0	65.36	120.98
15325009	8 X 0.75	8.7	83.99	153.1
15325010	2 X 1.0	6.7	31.42	76.14
15325011	3 X 1.0	7.0	41.97	89.46
15325012	4 X 1.0	7.4	52.9	105.59
15325013	6 X 1.0	8.5	81.75	144.07
15325014	8 X 1.0	9.2	105.4	180.36
15325015	2 X 1.5	7.6	44.09	98.95
15325016	3 X 1.5	7.9	65.53	121.02
15325017	4 X 1.5	8.5	82.14	145.09
15325018	6 X 1.5	9.8	117.22	196.01
15325019	8 X 1.5	10.8	151.94	249.75
15325020	2 X 2.5	8.8	75.42	141.64
15325021	3 X 2.5	9.2	102.07	173.32
15325022	4 X 2.5	10.0	129.75	210.67