

## ETHERLINE® ACCESS M

Industrial managed Ethernet switches

Industrial network switches for ethernet based solutions in Smart Factories.

### Info

Redundant power inputs

Robust metal housing and DIN rail mounting

Fanless – maintenance free



Supplementary automation components from Lapp



Mechanical and plant engineering

### Benefits

Improve your total cost of ownership with faster installation and lower downtime

Most flexible and globally present solutions from one hand

### Product features

Simple setup of redundant networktopologies with reconfiguration time < 20 ms

RJ45 Ports: 10/100/1000 BaseT(X)

Packet Buffer Size: 1 Mbit

Supported protocols: HTTPS/SSL, SSH, TACACS+, RADIUS, SNMP Client, Ethernet IP, Modbus TCP

Redundant Power Input: 24 VDC

### Norm references / Approvals

UL 61010

Shock IEC 60068-2-27

Freefall IEC60068-2-32

Vibration IEC 60068-2-6

Last Update (25.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ETHERLINE® ACCESS M

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000734 ETIM 5.0 Class-Description: Network switch
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000734 ETIM 6.0 Class-Description: Network switch
power supply:	DC 24 V (18-30 V DC)
Protection rating:	IP 40
Temperature range:	-40°C up to +75°C

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**ETHERLINE® ACCESS M**

Article number	Article designation	Type	number of ports
Managed Switches with SFP			
21700136	ETHERLINE® ACCESS M08T02SFP	Managed	8 x RJ45 + 2 x SFP
21700137	ETHERLINE® ACCESS M08T02GSFP	Managed	8 x RJ45 + 2 x SFP Gbit/s

Last Update (25.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03\_16