

## ETHERLINE® PN Cat.5 M12-RJ45

PROFINET Patchcord M12/RJ45

Industrial Ethernet Patchcord, Profinet Type A, Cat.5, plug M12 on plug RJ45, PVC

### Info

Based on 2170893

Additional variants are available at  
[www.lappgroup.com/assemblyfinder](http://www.lappgroup.com/assemblyfinder)  
 or on request.



Supplementary automation components from Lapp



Mechanical and plant engineering



Mechanical resistance



Assembly time



Interference signals



Waterproof

### Benefits

Non-permanent connections allow for easy change of equipment  
 For directly connecting two electric components

### Application range

Fixed Installation  
 suitable for EtherCAT and EtherNet/IP applications

Last Update (28.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ETHERLINE® PN Cat.5 M12-RJ45

Suitable for use in industrial applications  
For indoor use

### Product features

Meets the requirements according to Cat. 5e and class D  
2pair: 10/100 Mbit/s for Industrial Ethernet

### Norm references / Approvals

The cable is UL/CSA-certified (CMG)

### Product Make-up

Solid conductor, 2x2x AWG22/1  
Star quad  
Overall screening with copper braid and plastic-laminated aluminium foil  
Outer sheath made of PVC  
Colour: green (based on RAL 6018)  
Pre-assembled patchcords with D-coded M12 connector and RJ45-connector  
4 pole M12 connector with vibration protection

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC002599 ETIM 5.0 Class-Description: Patch cord copper (twisted pair) industry
Classification ETIM 6:	ETIM 6.0 Class-ID: EC002599 ETIM 6.0 Class-Description: Patch cord copper (twisted pair) industry
Minimum bending radius:	During installation: 15 x outer diameter Fixed installation: 10 x outer diameter
Protection rating:	M12 - IP69 RJ45 - IP20
Temperature range:	During installation: -20 °C to +60 °C Fixed installation: -40 °C to +80 °C

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Other lengths and types of connectors are available upon request.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

For detailed technical information please refer to the data sheet

# ETHERLINE® PN Cat.5 M12-RJ45

Article number	Article designation	Length (m)	Copper index kg/1.000 pieces
straight plug M12 on straight plug RJ45			
2171164	IE-PNA-5-M12D-S-0,5-Y-2-22-1-RJ45	0.5	15.2
2171165	IE-PNA-5-M12D-S-1-Y-2-22-1-RJ45	1	30.4
2171166	IE-PNA-5-M12D-S-2-Y-2-22-1-RJ45	2	60.8
2171167	IE-PNA-5-M12D-S-3-Y-2-22-1-RJ45	3	91.2
2171168	IE-PNA-5-M12D-S-5-Y-2-22-1-RJ45	5	152
2171169	IE-PNA-5-M12D-S-10-Y-2-22-1-RJ45	10	304
2171170	IE-PNA-5-M12D-S-20-Y-2-22-1-RJ45	20	608
angled plug M12 on straight plug RJ45			
2171171	IE-PNA-5-M12D-A-0,5-Y-2-22-1-RJ45	0.5	15.2
2171172	IE-PNA-5-M12D-A-1-Y-2-22-1-RJ45	1	30.4
2171173	IE-PNA-5-M12D-A-2-Y-2-22-1-RJ45	2	60.8
2171174	IE-PNA-5-M12D-A-3-Y-2-22-1-RJ45	3	91.2
2171175	IE-PNA-5-M12D-A-5-Y-2-22-1-RJ45	5	152
2171176	IE-PNA-5-M12D-A-10-Y-2-22-1-RJ45	10	304
2171177	IE-PNA-5-M12D-A-20-Y-2-22-1-RJ45	20	608

## ETHERLINE® PN Cat.5 M12-RJ45

