

# **UNITRONIC® BUS PB HEAT 180**

PROFIBUS cable with an extended temperature range up to +180°C

Bus cable for PROFIBUS-DP, -FMS and FIP. No need for additional cable protection against high temperatures. Oil resistance. Temp. range from -50 bis +180 °C

LAPP KABEL STUTTGART UNITRONIC® BUS PB HEAT 180





Supplementary automation components from Lapp



Mechanical and plant engineering



Oil-resistant



Temperature-resistant



**UV-resistant** 

#### **Benefits**

no need for additional cable protection against high temperatures High temperature resistance

#### **Application range**

Fixed Installation

For use in high temperature areas with up to 180 °C

#### **Product features**

High oil-resistance

### **Product Make-up**

Solid and bare copper conductor Wire insulation Fluorethylen

Last Update (23.04.2024) ©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16



## **UNITRONIC® BUS PB HEAT 180**

Overall screening with copper braid and plastic-laminated aluminium foil Outer sheath: FEP, violet (RAL 4001)

**Technical Data** 

Classification ETIM 5: ETIM 5.0 Class-ID: EC000830

ETIM 5.0 Class-Description: Data cable

Classification ETIM 6: ETIM 6.0 Class-ID: EC000830

ETIM 6.0 Class-Description: Data cable

Mutual capacitance: approx. 28 nF / km

Peak operating voltage: (not for power applications) 250 V
Minimum bending radius: Repeated: 7 x Outer Diameter

Single: 5 x Outer Diameter

Test voltage: 3600 V DC (3 sec.)

Characteristic impedance:  $(3 - 20 \text{ MHz}): 150 \pm 15 \text{ Ohm}$ 

Temperature range: -50 to +180 °C

#### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

SIMATIC® is a registered trademark of SIEMENS AG. FIP is a registered trademark of World FIP

Lapp Kabel is a member of the PROFIBUS user organisation (PNO)

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



**UNITRONIC® BUS PB HEAT 180** 

# Article number Article designation Number of pairs and conductor diameter (mm) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km) Number of pairs and conductor 2 Copper index (kg/km)