

PRODUCT INFORMATION

EPIC® SIGNAL M23 Inserts 12 pole

Inserts for M23 circular connectors

EPIC® SIGNAL M23 Inserts 12 pole for M23 circular connector series

Info Made in Germany







C€₽₽₩₩₩₩

Mechanical and plant engineering



Wind Energy



Good chemical resistance

Mechanical resistance

Assembly time

Robust

ĕ

Variety of approval certifications

Benefits

Universal further processing of the M23 inserts through different packaging units. Fully assembled with suitable solder contacts or unpopulated for individual assembly with crimp or solder contacts

Application range

Last Update (24.04.2024) ©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02_03.16



EPIC® SIGNAL M23 Inserts 12 pole

Plant engineering Measurement and control technology Apparatus construction

| Technical Data | | |
|--------------------------------|--|--|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000438 ETIM 5.0 Class-Description: Contact insert for industrial connectors | |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000438 ETIM 6.0 Class-Description: Contact insert for industrial connectors | |
| Rated voltage (V): | according to IEC 61984: 100 V | |
| Rated impulse voltage: | 1.5 kV | |
| Rated current (A): | 7 A | |
| Pollution degree: | 3 | |
| Contact resistance: | < 4 mOhm | |
| Contacts: | Gold-plated brass | |
| Number of contacts: | 12 12*1mm contacts | |
| Termination methods: | Crimp termination: 0.14 - 1.0 mm ² Solder termination: up to 1.0 mm ² | |
| Cycle of mechanical operation: | 100 | |
| VDE-tested: | Certified production control: VDE-REG. no. C24 (according to EN 61984, SELV according to DIN VDE 0100-410 has to be guaranteed) UL File Number: E249137 | |
| Temperature range: | -25°C up to +125°C | |
| | | |

Note

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-component and one Ecomponent. P-component = left turning (anticlockwise), E-component = right turning (clockwise) Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

| Article number | Article description | Inserts | Contacts included | Pin configuration | Pieces / PU |
|--------------------------|--|---------------------------|-------------------|-------------------|-------------|
| 12-pin inserts, P-part = | = rotation to the left (plug side anti | clockwise) | L | | |
| 73002712 | P-part | Unpopulated | - | 12 | 5 |
| 73002713 | P-part | Unpopulated | - | 12 | 20 |
| 73002714 | P-part | + male contacts, solder | 12 | 12 | 5 |
| 73002715 | P-part | + male contacts, solder | 12 | 12 | 20 |
| 73002716 | P-part | + female contacts, solder | 12 | 12 | 5 |
| 73002717 | P-part | + female contacts, solder | 12 | 12 | 20 |
| 12-pin inserts, E-part = | rotation to the right (plug side cloped and the right) | ckwise) | | | |
| 73002718 | E-Part | Unpopulated | - | 12 | 5 |
| 73002719 | E-Part | Unpopulated | - | 12 | 20 |
| 73002720 | E-Part | + male contacts, solder | 12 | 12 | 5 |
| 73002721 | E-Part | + male contacts, solder | 12 | 12 | 20 |
| 73002722 | E-Part | + female contacts, solder | 12 | 12 | 5 |
| 73002723 | E-Part | + female contacts, solder | 12 | 12 | 20 |

® LAPP

EPIC® SIGNAL M23 Inserts 12 pole





EPIC® SIGNAL M23 Inserts 12 pole











Last Update (24.04.2024) ©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de You can find the current technical data in the corresponding data sheet. PN 0456 / 02_03.16