

Innovative metal and plastic housing design

The robust housing with an open bottom and 2 cable entries can be used in control systems or other applications in restricted spaces.

Info

Lightweight, chemically resistant plastic housing Protection rating UL50E tested











Mechanical and plant engineering



Mechanical resistance



Robust



Waterproof

Benefits

Housing in plastic or metal version for safe connections in the smallest possible space $\,$

Application range

Machine and equipment manufacturing Control engineering Electronic laboratory

Product features

Surface-mount base 1 lever 2 cable entries

Last Update (24.04.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16



Housing type: with open base

Included: flat gasket

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material: Housing: powder-coated zinc die-casting, grey

Lever: zinc-plated steel

Sealing: NBR

Housing: grey thermoplastic, black

Lever: zinc-plated steel

Sealing: NBR

Protection rating: IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested: Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range: -40°C to +100°C, short-term up to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



М Colour Pieces / PU Article number Article description Material H-A housing: surface-mount base (with open base) 20 H-A 3 MAgsv M20 Zinc die-casting 10 19517200 grey 19515200 H-A 3 Agsv M20 20 Thermoplastic 10 grey



