
# EPIC® H-D 64 machined


Multi-pole inserts for machined crimp contacts


The insert for rectangular connectors is ideal for use in applications requiring a high number of contacts. These can be found, for example, in investment constructions.

## Info

For machined contacts for fast processing with the crimping tool
Made in Europe








Mechanical and plant engineering

Space requirement

Robust

## Benefits

Inserts of the connector series H-D are designed for applications in which a high number of contacts are required.

## Application range

Plant engineering
Light & sound technology

## Technical Data

| | |
|---|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000438<br>ETIM 5.0 Class-Description: Contact insert for industrial connectors |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000438<br>ETIM 6.0 Class-Description: Contact insert for industrial connectors |

Last Update (05.03.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

# EPIC® H-D 64 machined

| | |
|---|---|
| Rated voltage (V): | IEC: 250 V<br>UL: 250 V |
| Rated impulse voltage: | 2.5 kV |
| Rated current (A): | IEC: 10 A<br>UL: 10 A |
| Pollution degree: | 3 |
| Contact resistance: | < 2 mOhm |
| Contacts: | Copper alloy, hard silver/gold-plated |
| Number of contacts: | 64 + PE |
| Termination methods: | Crimp termination: 0.14 - 2.5 $mm^2$ |
| Cycle of mechanical operation: | 100 |
| Certifications: | UL-tested:<br>UL File Number: E75770 |
| Temperature range: | -40 °C to +100 °C, short-term up to +125 °C |

**Note**
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.


©2024 Lapp Group - Technical changes reserved

LAPP

PRODUCT INFORMATION

# EPIC® H-D 64 machined

| Article number | Article description | Contact type | Article designation | Number of operating contacts | Pieces / PU |
|---|---|---|---|---|---|
| 11272000 | H-D 64 SCM | male | machined | 1 - 64 | 10 |
| 11273000 | H-D 64 BCM | female | machined | 1 - 64 | 10 |

Last Update (05.03.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16