

EPIC® H-EE 64


H-EE inserts with high contact density based on the proven H-BE series.

The insert with a high density of contacts is intended for medium power outputs and is ideal for investment construction and mechanical engineering.

Info
Inserts with high contact density for medium power







Mechanical and plant engineering

Temperature-resistant

Benefits
The H-EE inserts with machined contacts for a high number of pins in very tight spaces.
For assembly in H-B housing

Application range
Mechanical engineering
Plant engineering
Appliance and apparatus construction

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000438 ETIM 5.0 Class-Description: Contact insert for industrial connectors
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000438 ETIM 6.0 Class-Description: Contact insert for industrial connectors
Rated voltage (V):	IEC: 500 VUL: 600 VCSA: 600 V
Rated impulse voltage:	6 kV

Last Update (27.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

EPIC® H-EE 64

Rated current (A):	IEC: 16 A UL: 16 A CSA: 16 A
Pollution degree:	3
Contact resistance:	< 2 mOhm
Contacts:	Copper alloy, hard silver/gold-plated
Number of contacts:	32 + PE
Termination methods:	Crimp termination: 0.5 - 4.0 mm^2
Cycle of mechanical operation:	100
Temperature range:	-40 °C to +100 °C, short-term up to +125 °C

Note
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2024 Lapp Group - Technical changes reserved

LAPP

EPIC® H-EE 64

PRODUCT INFORMATION

Article number	Article description	Contact type	Article designation	Number of operating contacts	Pieces / PU
H-EE 64 crimp termination					
10184500	H-EE 32 SC	male	machined	33 - 64	5
10185500	H-EE 32 BC	female	machined	33 - 64	5

Last Update (27.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16