

EPIC® H-Q TG

There are many different uses for this sturdy rectangular connector hood made of plastic. The M25 female thread is suitable for connecting a separate cable or conduit gland. This results in an optimised design with regard to weight and installation space.



Corrosion-resistant



Low weight



Optimum strain relief



Space requirement

Benefits

The hood housing is mateable with many commercially available housings (panel-mount base, surface-mount base or coupler hood housings).

Space and weight-saving due to the small size.

With space-saving female thread for use with metric cables or conduit glands.

Locking takes place using a central lever on the counter-housing.

Corresponds to protection class IP 65 when locked.

Application range

To protect the connector insert from environmental influences.

For use with rectangular connector inserts in the EPIC®H-Q series.

For power supply connection of devices and machines in various applications.

Withstands high environmental and mechanical stresses.

Typical areas of application are electric motors and servo drives.

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material:

Housing: thermoplastic, grey

Lever: metal

Protection rating:

IP 65

Last Update (16.07.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

EPIC® H-Q TG

Temperature range: -40°C to +125°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® H-Q TG

Article number	M	Packaging unit
381166440	25	10

Last Update (16.07.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16