

EPIC® MC module: HC4+PE

The mixed assembly guarantees high flexibility. For applications in machine and plant engineering, for robotics and slide-in technology.

The high-voltage signal and power module combine a greater number of functions, which ensures a high level of flexibility. It can be used, for example, in robotics.

Info

Suitable for processing with contacts on reel for automated production with crimping machine





Supplementary automation components from Lapp



Mechanical and plant engineering



Wind Energy

Benefits

The mix of different functions in one plug guarantees high flexibility Assembly of individual connectors, suitable for different applications

Application range

Plant engineering Printing machines Control engineering

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC002641

ETIM 5.0 Class-Description: Modular connector (industrial

connector)

Classification ETIM 6: ETIM 6.0 Class-ID: EC002641

ETIM 6.0 Class-Description: Modular connector (industrial

connector)

Rated voltage (V): 1000 V
Rated current (A): 16 A

Last Update (24.07.2024) ©2024 Lapp Group - Technical changes reserved Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16





EPIC® MC module: HC4+PE

Pollution degree: 3

Contact resistance: < 2 mOhm

Contacts: Copper alloy, hard silver-plated

Number of contacts: 4 + PE

Termination methods: Crimp termination: 0.5 - 2.5 mm²

Cycle of mechanical operation: 100

Temperature range: -40 °C to +100 °C, short-term up to +125 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® MC module: HC4+PE

Contact type Number of operating contacts | Slots Packaging unit Article number Article description Module: high voltage 4-pin + PE MCS 5 CG 4 + PE 10 10383200 male MCB 5 CG 4 + PE 10 10383300 female