

EPIC® MH Potential set

High flexibility by the use of any combination of inserts in one connector

Potential spring for EPIC® MH multi frame

Info

Potential spring for EPIC® MH multi frame





Supplementary automation components from Lapp



Mechanical and plant engineering



Rail



Wind Energy

Benefits

Potential spring for EPIC® MH multi frame For use in EPIC® MH BUS modules Two springs can be used for an EPIC® MH BUS module

Application range

Mechanical engineering Robotics industry Plant engineering Renewable energy Railway applications / vehicle construction

Technical Data

Classification ETIM 5: ETIM 5.0 Class-ID: EC000796

ETIM 5.0 Class-Description: Contact for industrial connectors

Classification ETIM 6: ETIM 6.0 Class-ID: EC000796

ETIM 6.0 Class-Description: Contact for industrial connectors

-40°C to +125°C

Last Update (24.04.2024)

Temperature range:

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16



EPIC® MH Potential set

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® MH Potential set

Article number Article description Contact type Pieces / PU 44423265 EPIC® MHS Potential Set male 20 44423275 EPIC® MHB Potential Set female 20