

FLEXIMARK® Flexilabel TFL

FLEXIMARK® Flexilabel TFL are blank label rolls for marking cables with character holders or for installation. Text can be printed on the labels using our marking software with a thermal transfer printer.



Good chemical resistance



Halogen-free



UV-resistant

Benefits

Suitable labels for PTE, PTEF and CAB character holders (see chapter "Character holders and accessories")
 Suitable for IP20 - IP40 Environments like public buildings such as schools, offices, hospital and malls

Application range

Installation labels
 For cable marking

Note

Easy to print via FLEXIMARK® software Flexisoft and FLEXIMARK® thermal transfer printer SQUIX, EOS5 or EOS2

Included

Delivered as a roll of labels

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001288
 ETIM 5.0 Class-Description: Labelling material

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001288
 ETIM 6.0 Class-Description: Labelling material

Colour delivered:

White or yellow
 Upon request: Yellow, green, blue, red, brown, black

Material:

Halogen-free polyester
 Polypropylene laminate

Last Update (24.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

FLEXIMARK® Flexilabel TFL

Temperature range: -20°C to +80°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

FLEXIMARK® products are sold in packaging units. As example if you like to order 640 labels of LCK 32 you just need to order 1 PU instead of 640 single labels.

FLEXIMARK® Flexilabel TFL

Article number	Article designation	Colour	Width x length (mm)	Markers / PU	PU
83254605	FLEXIMARK® Flexilabel TFL 9.5-28 YE	yellow	9.5 x 28.0	1000	1
83254610	FLEXIMARK® Flexilabel TFL 9,5-35 YE	yellow	9.5 x 35.0	1000	1

Last Update (24.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16