

FLEXIMARK® THERMO CLIP Starter Kit

Starter kit as basic equipment with FLEXIMARK® THERMO CLIP temperature indicators, in a stable and stackable case, with small part inserts and a transparent cover.



Mechanical and plant engineering



Assembly time

Benefits

Starter kit as basic equipment with FLEXIMARK® THERMO CLIP temperature indicators in five different sizes for a cable outer diameters of 2.3 – 31.0 mm.

The use of small parts ensures optimum order and prevents the content from being mixed up. The size of the individual compartments can be individually adapted.

Stackable and robust case made of durable plastic.

The transparent lid provides a perfect overview, even when closed.

The snap closure provides reliable closing.

Application range

For safe transport and storage of FLEXIMARK® THERMO CLIP temperature indicators.

Especially for use in maintenance, e.g. for inspecting industrial plants.

Note

Limitations: FLEXIMARK® THERMO CLIP series are suitable for use on 600 VAC/VDC max rated wire insulation. FLEXIMARK® THERMO CLIP series are not suitable for unprotected use outdoors or in direct sunlight. The clips are vulnerable to degradation and non-performance from prolonged exposure to ultra-violet (UV) light. FLEXIMARK® THERMO CLIP series are not suitable for use in sub-zero temperatures. FLEXIMARK® THERMO CLIP series will not prevent electrical faults or fires but will aid in monitoring abnormal temperatures and will give visual indication of abnormal wire insulation temperature above 71 °C for whatever underlying cause. Use of FLEXIMARK® THERMO CLIP series does not replace the need to formally inspect, test, maintain and install electrical installations in accordance with locally applicable: electrical installation/inspection/maintenance codes; health and safety requirements and manufacturer's instructions. This information is provided solely for consideration, investigation, and verification by the user. FLEXIMARK® THERMO CLIP series are not suitable for all environmental applications. The end user must verify that they are suitable for use in their application.

Technical Data

Classification ETIM 5:

EC003592

On request:

Further dimensions and symbols

Last Update (26.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

FLEXIMARK® THERMO CLIP Starter Kit

| | |
|--------------------|--|
| Colour delivered: | Purple |
| Material: | 5-10% Thermochromic Masterbatch. 90-95% Polypropylene, nonhalogenated (Halogen-free). |
| Temperature range: | Reversible colour change at temperatures of +53 °C to +70 °C. Irreversible colour change at temperatures from +71 °C. |

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

FLEXIMARK® products are sold in packaging units. As example if you like to order 640 labels of LCK 32 you just need to order 1 PU instead of 640 single labels.



FLEXIMARK® THERMO CLIP Starter Kit

| |
|----------------|
| Article number |
| 83881140 |

Last Update (26.04.2024)

©2024 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16