CHARGE M3 T3P/T1C S

Charge charging cable with type 3, type 1 connector, length 5m or 7m for connection between charging station and electro vehicle

Info
For electric vehicles with type 1 vehicle inlet



- e-Mobility
- Suitable for outdoor use
- Cold-resistant
- Mechanical resistance
- Oil-resistant
- Robust
- UV-resistant

Benefits
new two-chamber system for environmental protection of moving parts to the connection part
Resistant to oil, dust and water
Special cable design for a long service life
Flexible at low temperatures
Withstands high mechancal stress, in particular abrasion and sliding demands

Application range

Last Update (22.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

CHARGE M3 T3P/T1C S

For charging stations, electric and Plug-in Hybrid vehicles

Product Make-up

Cable for 1-phase charging up to 20A: ÖLFLEX® Charge 3G2.5 mm^2+1x0.5 mm^2
Cable for 1-phase charging up to 32A: ÖLFLEX® Charge 3G6mm^2+1x0,5mm^2

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC002839 ETIM 5.0 Class-Description: Accessories for battery/charger
Certifications:	according to VDE-AR-E2283-5 according to EN 61851-1
Temperature range:	Flexing: -30 °C to +50 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.
Further colour combinations and lengths on request

©2024 Lapp Group - Technical changes reserved

LAPP

CHARGE M3 T3P/T1C S

PRODUCT INFORMATION

Article number	Version	Effective length (mm)	Copper index kg/1.000 pieces	Weight (kg/1000 pieces)	PU
Plug type 3, charging cable, vehicle connector type 1					
74880173	Charging: 1 phase 20A	5000	414	1540	1
74880174	Charging: 1 phase 32A	5000	959	2400	1

Last Update (22.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16