


SILVYN® BRAID PA6

SILVYN® BRAID PA6 is a braided sleeving to protect cables from abrasion

Info

Simple, fast cable bundling



Wide clamping range



Low weight



Reliability



Temperature-resistant



UV-resistant

Benefits

Can be cut without the need for a thermo-cutting tool

Cut into length without frizzle on the conduit's end

Abrasion protection

Simple, fast cable bundling

Protection against dust

Application range

Easy cable protection

Additional insulation

Bundling and guiding of cables and wires

Low rodent-protection

Product features

Abrasion-resistant

Flexible

Can be cut at cold temperatures

Last Update (23.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® BRAID PA6

Product Make-up

Polyamide 6.6 - halogen-free

Technical Data

| | |
|------------------------|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC001182 ETIM 5.0 Class-Description: Braided hose |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC001182 ETIM 6.0 Class-Description: Braided hose |
| On request: | Bulk containers on rolls More sizes available |
| Note: | Halogen and cadmium-free Fire behaviour according to UL94 V-2 |
| Colour delivered: | Black (RAL 9005), UV-resistant |
| Material: | Polyamide 6.6 - halogen-free |
| Temperature range: | -55°C to +125°C |

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

SILVYN® BRAID PA6

| Article number | Nominal size | Clamping range in mm | Colour | PU (m) |
|-------------------|--------------|----------------------|--------|--------|
| SILVYN® BRAID PA6 | | | | |
| 61721260 | 6 | 4 - 10 | black | 20 |
| 61721261 | 12 | 10 - 14 | black | 15 |
| 61721262 | 16 | 14 - 24 | black | 15 |
| 61721263 | 20 | 18 - 26 | black | 10 |
| 61721264 | 30 | 26 - 34 | black | 10 |
| 61721265 | 40 | 32.0 - 42.0 | black | 5 |

Last Update (23.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16