SILVYN® SHRINK BRAID PET

SILVYN® SHRINK BRAID PA6 - shrinkable braided sleeving

Info
Shrinkable abrasion protection





- Wide clamping range
- Low weight
- Reliability
- Temperature-resistant
- UV-resistant

Benefits
Additional abrasion protection for critical areas
Cut into length without frazzle on the conduit's end
Simple, fast cable bundling
Protection against dust

Application range
Easy cable protection
Additional insulation
Bundling and guiding of cables and wires
Low rodent-protection

Product features
Abrasion-resistant
Flexible
Shrinkable
Shrinking ratio: 2:1
Maximum length lost after shrinkage is less than 15 %

Last Update (23.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SILVYN® SHRINK BRAID PET

Product Make-up
Polyester - PET with shrinkable Polyolefin fibres

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001182 ETIM 5.0 Class-Description: Braided hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001182 ETIM 6.0 Class-Description: Braided hose
On request:	Bulk containers on rolls More sizes available
Note:	No dielectric strength Self extinguishing acc. to UL94 HB
Colour delivered:	Black (RAL 9005), UV-resistant
Material:	Polyester - PET with shrinkable Polyolefin fibres
Temperature range:	-40 °C to +150 °C Processing: min. +180 °C

Note
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2024 Lapp Group - Technical changes reserved

SILVYN® SHRINK BRAID PET

Article number	Nominal size	Shrinkage range mm	Colour	PU (m)
SILVYN® SHRINK BRAID PET				
61721270	12/06	12 - 6	black	5
61721271	25/12	25 - 12	black	5
61721272	30/15	30 - 15	black	5
61721273	50/25	50 - 25	black	4
61721274	70/35	70 - 35	black	4

Last Update (23.02.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16