SILVYN® LKI

SILVYN® LKI - swivelling plastic conduit fitting

Info
Swivelling upper part with integrated inner sleeve

Maximum vibration protection

Assembly time

Space requirement

Benefits
Fast and easy assembly
Vibration protection
High-tensile
Can be rotated

Application range
In combination with protective conduit:
SILVYN® FPS
SILVYN® FD-PU
Robot-building
For rotating applications

Product features
Smooth inner surface
Slim construction

Product Make-up

Last Update (24.04.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

SILVYN® LKI

PG connection thread
Swivelling upper part with integrated inner sleeve

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001178 ETIM 5.0 Class-Description: Screw connection for protective plastic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001178 ETIM 6.0 Class-Description: Screw connection for protective plastic hose
Colour delivered:	Silver grey (RAL 7001)
Material:	PP
Protection rating:	IP 54
Temperature range:	-10 °C to +110 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

©2024 Lapp Group - Technical changes reserved

LAPP

SILVYN® LKI

PRODUCT INFORMATION

Article number	PG size	SW wrench size mm	Overall length mm	Thread length mm	Clear opening (mm)	Suitable for SILVYN® FPS/FD-PU	Pieces / PU
SILVYN® LKI							
55000000	7	16	38	10	5.5	7 x 10	50
55000010	9	19	39.5	10	9.5	10 x 14	50
55000020	11	22	42	10	11.5	13 x 17	50
55000030	13.5	24	42	10	13	15 x 19	50
55000040	16	27	48	11	14.5	16 x 21	50
55000050	21	35	58	11	19.5	22 x 27	25
55000060	29	45	59	12	27	29 x 36	25
55000070	36	54	62.5	12	35.5	38 x 45	25
55000090	48	65	68	15	46	48 x 56	10

Last Update (24.04.2024)
©2024 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16