

## SILVYN® CNP NPT

SILVYN® CNP conduit gland is made of nickel-plated brass for use with SILVYN® CNP



Good chemical resistance



Corrosion-resistant



Mechanical resistance

### Benefits

Flame-retardant  
High tensile strength  
For high mechanical stress  
High chemical-resistance

### Application range

Mechanical engineering  
Robot-building  
Vending machine construction  
Exporters

### Product Make-up

The basic body is made of cast steel with a galvanised surface. The inner sleeve is made of polyamide and accommodates the conduit. A special profile on the inner sleeve is pressed into the conduit by the union nut including O-ring and counter nut

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001180

ETIM 5.0 Class-Description: Screw connection for protective metallic hose

Classification ETIM 6:

ETIM 6.0 Class-ID: EC001180

Last Update (31.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**SILVYN® CNP NPT**

	ETIM 6.0 Class-Description: Screw connection for protective metallic hose
Material:	Body: cast steel with zinc-plated surface Inner sleeve: PA
Protection rating:	IP 67
Temperature range:	-45°C to +105°C

**Note**

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SILVYN® CNP NPT**

Article number	Nominal size	SW wrench size mm	Overall length mm	Suitable for SILVYN® CNP	Pieces / PU
SILVYN® CNP NPT fitting					
55500400	1/2"	27	55	3/8"	1
55500410	1/2"	32	66	1/2"	1
55500420	3/4"	39	66	3/4"	1
55500430	1"	45	73	1"	1
55500440	1 1/4"	59	87	1 1/4"	1
55500450	1 1/2"	67	87	1 1/2"	1
55500460	2"	82	101	2"	1

Last Update (31.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16