

Ty-Rap® Cable tie with steel nose for screwing on

The TY- RAP® with steel nose is also available as cable tie for assembly with screws, bolts and rivets.



Halogen-free

Benefits

Cable ties with fasteners
 Allow installation and bundling in one step
 Steel nose ensures secure and durable binding

Application range

For assembly with screws, bolts and rivets
 Simultaneous installation and bundling
 Possible application areas: Cable assemblies, pre- and final installation of parts and bundles, and for maintenance-free installation of cables and ducts

Norm references / Approvals

File number: E49405, see table
 Fire behaviour according to UL94 V-2

Design

Also deliverable in black and UV-resistant

Technical Data

| | |
|------------------------|--|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000046 ETIM 5.0 Class-Description: Cable tie |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000046 ETIM 6.0 Class-Description: Cable tie |
| Colour delivered: | Natural colour |
| Material: | Polyamide 6.6 Halogen-free and silicone-free |
| Temperature range: | -40°C to +85°C |

Last Update (01.06.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

Ty-Rap® Cable tie with steel nose for screwing on

Note

TY-RAP® is a registered trademark of ABB.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Ty-Rap® Cable tie with steel nose for screwing on

| Article number | Article description | UL certification | Hole Ø (mm) | Length x width (mm) | Bundling Ø (mm) | Tensile strength (N) | Pieces / PU |
|----------------|---------------------|------------------|-------------|---------------------|-----------------|----------------------|-------------|
| 61715420 | TY 33 M | yes | 2.8 | 102.0 x 2.3 | 2 - 16 | 80 | 1000 |
| 61715480 | TY 34 M | yes | 4.2 | 151.0 x 3.5 | 2 - 29 | 180 | 1000 |
| 61720000 | TY 635 M | yes | 3.5 | 198.0 x 4.7 | 3.5 - 45 | 220 | 1000 |
| 61715540 | TY 35 M | yes | 4.8 | 199.0 x 4.7 | 3.5 - 45 | 220 | 1000 |
| 61720070 | TY 1435 M | yes | 6.3 | 198.0 x 4.7 | 3.5 - 45 | 220 | 1000 |
| 61715600 | TY 37 M | yes | 6.3 | 356.0 x 7.7 | 6 - 90 | 540 | 500 |

Last Update (01.06.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16